

Field Measurements on the Effect of Temporary Rumble Strips in Work Zone Flagging Operations

Final Report
May 2017



Center for Transportation
Research and Education



Sponsored by

Iowa Department of Transportation
Midwest Transportation Center
U.S. Department of Transportation
Office of the Assistant Secretary for
Research and Technology



IOWA STATE UNIVERSITY
Institute for Transportation

About MTC

The Midwest Transportation Center (MTC) is a regional University Transportation Center (UTC) sponsored by the U.S. Department of Transportation Office of the Assistant Secretary for Research and Technology (USDOT/OST-R). The mission of the UTC program is to advance U.S. technology and expertise in the many disciplines comprising transportation through the mechanisms of education, research, and technology transfer at university-based centers of excellence. Iowa State University, through its Institute for Transportation (InTrans), is the MTC lead institution.

About InTrans

The mission of the Institute for Transportation (InTrans) at Iowa State University is to develop and implement innovative methods, materials, and technologies for improving transportation efficiency, safety, reliability, and sustainability while improving the learning environment of students, faculty, and staff in transportation-related fields.

About CTRE

The mission of the Center for Transportation Research and Education (CTRE) at Iowa State University is to develop and implement innovative methods, materials, and technologies for improving transportation efficiency, safety, and reliability while improving the learning environment of students, faculty, and staff in transportation-related fields.

ISU Non-Discrimination Statement

Iowa State University does not discriminate on the basis of race, color, age, ethnicity, religion, national origin, pregnancy, sexual orientation, gender identity, genetic information, sex, marital status, disability, or status as a U.S. veteran. Inquiries regarding non-discrimination policies may be directed to Office of Equal Opportunity, 3410 Beardshear Hall, 515 Morrill Road, Ames, Iowa 50011, Tel. 515-294-7612, Hotline: 515-294-1222, email eooffice@iastate.edu.

Notice

The contents of this report reflect the views of the authors, who are responsible for the facts and the accuracy of the information presented herein. The opinions, findings and conclusions expressed in this publication are those of the authors and not necessarily those of the sponsors.

This document is disseminated under the sponsorship of the U.S. DOT UTC program in the interest of information exchange. The U.S. Government assumes no liability for the use of the information contained in this document. This report does not constitute a standard, specification, or regulation.

The U.S. Government does not endorse products or manufacturers. If trademarks or manufacturers' names appear in this report, it is only because they are considered essential to the objective of the document.

Quality Assurance Statement

The Federal Highway Administration (FHWA) provides high-quality information to serve Government, industry, and the public in a manner that promotes public understanding. Standards and policies are used to ensure and maximize the quality, objectivity, utility, and integrity of its information. The FHWA periodically reviews quality issues and adjusts its programs and processes to ensure continuous quality improvement.

Technical Report Documentation Page

1. Report No.	2. Government Accession No.	3. Recipient's Catalog No.	
4. Title and Subtitle Field Measurements on the Effect of Temporary Rumble Strips in Work Zone Flagging Operations		5. Report Date May 2017	
		6. Performing Organization Code	
7. Author(s) Neal Hawkins and Skylar Knickerbocker		8. Performing Organization Report No.	
9. Performing Organization Name and Address Center for Transportation Research and Education Institute for Transportation Iowa State University 2711 South Loop Drive, Suite 4700 Ames, IA 50010-8664		10. Work Unit No. (TR AIS)	
		11. Contract or Grant No. Part of DTRT13-G-UTC37	
12. Sponsoring Organization Name and Address Midwest Transportation Center U.S. Department of Transportation 2711 S. Loop Drive, Suite 4700 Office of the Assistant Secretary for Ames, IA 50010-8664 Research and Technology Iowa Department of Transportation 1200 New Jersey Avenue, SE 800 Lincoln Way Washington, DC 20590 Ames, IA 50010		13. Type of Report and Period Covered Final Report	
		14. Sponsoring Agency Code	
15. Supplementary Notes Visit www.intrans.iastate.edu for color pdfs of this and other research reports.			
16. Abstract Limited-scale field measurements were collected to quantify the impact of two temporary rumble strip (TRS) layouts at two different two-lane roadway construction projects in Iowa. The field work was not designed to produce statistically valid comparisons for TRS effectiveness, nor contrast between TRS layouts, work zone project locations, or measured locations per site. The findings are not comprehensive or consistent with any type of before/after or test/control evaluation. However, given the results, the presence of temporary rumble strips were found to have the following impacts as vehicles approached the work zones: <ul style="list-style-type: none"> • Increased driver braking • Minimal driver avoidance (driving around the rumble strips) • Reduced vehicle speeds These field data are considered positive and should serve future study efforts in terms of hypothesis development and testing as part of a controlled evaluation.			
17. Key Words driver behavior—one-lane flagging operations—temporary rumble strips—two-lane roadway construction—work zone safety		18. Distribution Statement No restrictions.	
19. Security Classification (of this report) Unclassified.	20. Security Classification (of this page) Unclassified.	21. No. of Pages 20	22. Price NA

FIELD MEASUREMENTS ON THE EFFECT OF TEMPORARY RUMBLE STRIPS IN WORK ZONE FLAGGING OPERATIONS

**Final Report
May 2017**

Principal Investigator

Neal Hawkins, Associate Director
Institute for Transportation, Iowa State University

Co-Principal Investigator

Skylar Knickerbocker, Engineer
Center for Transportation Research and Education, Iowa State University

Authors

Neal Hawkins and Skylar Knickerbocker

Sponsored by

Iowa Department of Transportation,
Midwest Transportation Center, and
U.S. Department of Transportation
Office of the Assistant Secretary for Research and Technology

Preparation of this report was financed in part
through funds provided by the Iowa Department of Transportation
through its Research Management Agreement with the
Institute for Transportation

A report from

**Institute for Transportation
Iowa State University**

2711 South Loop Drive, Suite 4700
Ames, IA 50010-8664

Phone: 515-294-8103 / Fax: 515-294-0467

www.intrans.iastate.edu

TABLE OF CONTENTS

ACKNOWLEDGMENTS	vii
BACKGROUND, OBJECTIVES, AND OVERVIEW	1
SCOPE	5
DATA COLLECTION METHODOLOGY	5
FIELD EVALUATION	6
2015 Field Evaluation	6
2016 Field Evaluation	7
RESULTS	7
Braking Measurement	7
Braking and Avoidance Findings.....	8
Speed Measurement	10
Speed Findings.....	10
SUMMARY	12

LIST OF FIGURES

Figure 1. Temporary rumble strips1
Figure 2. Iowa DOT TRS Developmental Specification2
Figure 3. No TRS setup3
Figure 4. With Iowa DOT TRS layout from Developmental Specification (two sets of
temporary rumble strips4
Figure 5. With modified TRS layout/setup (single set of rumble strips and Rumble Strips
Ahead advance warning sign).....4
Figure 6. Trailer placement.....5
Figure 7. US 52 evaluation in 20156
Figure 8. IA 92 evaluation in 20167
Figure 9. Vehicle braking measurement locations relative to TRS setup locations8
Figure 10. Vehicle speed measurement locations relative to TRS setup locations10

LIST OF TABLES

Table 1. Hours of data collected7
Table 2. Upstream braking and avoidance by setup8
Table 3. Downstream braking and avoidance by setup8
Table 4. Advance location speeds.....10
Table 5. After upstream TRS speeds11
Table 6. Impact on mean speeds11

ACKNOWLEDGMENTS

The authors would like to thank the Midwest Transportation Center and the U.S. Department of Transportation Office of the Assistant Secretary for Research and Technology for sponsoring this research. The Iowa Department of Transportation provided match funds for this project.

BACKGROUND, OBJECTIVES, AND OVERVIEW

In 2013, the Iowa Department of Transportation (DOT) began working with industry to consider the use of temporary rumble strips (TRS), shown in Figure 1, as part of flagging operations on two-lane roads.



Figure 1. Temporary rumble strips

This issue was brought to the Roadway Industry Safety Consensus (RISC) committee, which includes both Iowa DOT and contractor/industry representatives.

One objective of the group was to further understand the effectiveness of TRS, because the Iowa DOT is considering making them a standard for work zones on two-lane roadways. The group also wanted some field verification on the effectiveness of the rumble strips in alerting drivers to the presence of a work zone and in reducing vehicle speeds as drivers approach the one-way/one-lane flagging operation. However, the group did not have any available funding to conduct an evaluation.

As a starting point, limited-scale field measurements were conducted to quantify the impact of the TRS devices at two different construction projects over different years (one location in 2015 and one in 2016). In both cases, field measurements were coordinated between the project contractor and Iowa DOT construction staff.

Figure 2 shows the Iowa DOT Developmental Specification used by contractors to place the temporary rumble strips.




Figure 2. Iowa DOT TRS Developmental Specification




Figure 4. With Iowa DOT TRS layout from Developmental Specification (two sets of temporary rumble strips)




Figure 5. With modified TRS layout/setup (single set of rumble strips and Rumble Strips Ahead advance warning sign)

SCOPE

This limited field evaluation provides some quantification and visual recording of TRS impacts within one-lane flagger-operated work zones in Iowa. The measures of effectiveness include the following:

- Driver braking
- Avoidance (driving around the rumble strips)
- Change in speed

DATA COLLECTION METHODOLOGY

Figure 6 shows how data collection trailers were oriented for both video and speed data, with a trailer placed in advance of each set of TRS.




Figure 6. Trailer placement

The field evaluation included only one approach direction per work zone. In each case, the data collection trailer setup was moved along with the work area.

FIELD EVALUATION

The field evaluations were conducted for a different single work zone in 2015 and 2016.

2015 Field Evaluation

- Location: District 2 - US 52 (near Calmar)
- Evaluation Timeframe: June/July 2015



Figure 7. US 52 evaluation in 2015

2016 Field Evaluation

- Location: District 5 - IA 92 (near Oskaloosa)
- Evaluation Timeframe: August 2016




Figure 8. IA 92 evaluation in 2016

RESULTS

The findings from both the 2015 and 2016 field evaluations are presented below for braking, avoidance (driving around the rumble strips), and vehicle speed.

Table 1 lists the number of hours of data collection for each field scenario observed.

Table 1. Hours of data collected

Setup	Hours
No TRS	9.25
Iowa DOT TRS layout	20.50
Modified TRS layout	9.75

Braking Measurement

The braking observations are provided at two different points (upstream and downstream) and contrasted by TRS setup, which included the following:

- No TRS – Without TRS setup (see previous Figure 3)
- Standard – With TRS setup using the Iowa DOT Developmental Specification layout (see previous Figure 4)
- Modified – With modified TRS setup/layout (only one set of rumble strips and advance Rumble Strips Ahead warning sign) (see previous Figure 5)

Figure 9 identifies the observed braking locations for the Iowa DOT layout by number (within a circle) where:

- Location 1: Upstream TRS before the rumble
- Location 2: Upstream TRS after the rumble
- Location 3: Downstream TRS before the rumble
- Location 4: Downstream TRS after the rumble




Figure 9. Vehicle braking measurement locations relative to TRS setup locations

Braking and Avoidance Findings

Tables 2 and 3 summarize the results of the video analysis for vehicle braking and driving around the TRS for upstream and downstream, respectively.

Table 2. Upstream braking and avoidance by setup

Setup	No TRS	Standard	Modified
Braking before rumble	9%	18%	26%
Braking after rumble	1%	11%	8%
Overall braking	10%	29%	33%
Driving around rumble	NA	1%	1%
Number driving around rumble	NA	12	3

Table 3. Downstream braking and avoidance by setup

Setup	No TRS	Standard	Modified
Braking before rumble	18%	23%	30%
Braking after rumble	5%	2%	14%
Overall braking	33%	25%	45%
Driving around rumble	NA	3%	NA
Number driving around rumble	NA	27	NA

Upstream TRS Setup Findings

- TRS presence increased braking behavior.
 - In contrast to no TRS setup, drivers hit their brakes twice as much under the standard TRS layout and almost three times as much under the modified TRS layout (which included an advance Rumble Strips Ahead warning sign). The percent of drivers braking after the upstream TRS setup increased from 1 to 11 percent (no TRS setup versus standard layout) and 8 percent under the modified layout. The 3 percent difference between TRS layouts is small but could reflect that, under the modified scenario, more drivers had already hit their brakes prior to the rumble strips.
 - The overall percentage of drivers braking increased by roughly a factor of 3 when rumble strips were present.
- TRS avoidance was minimal (1 percent).

Downstream TRS Setup Findings

- TRS presence increased braking behavior.
 - The modified layout did not have a TRS setup at the downstream location. These observations reflect the general spot where the downstream TRS setup was under the standard layout.
 - In contrast to no TRS setup, drivers hit their brakes 27 to 67 percent more when facing the standard and modified layouts, respectively. The percent of drivers braking after the downstream TRS setup actually decreased from 5 to 2 percent (no TRS setup versus standard layout) and increased to 14 percent under the modified layout. The decrease observed for the standard layout is small but could reflect the visibility of the queue ahead and the implied need to slow down.
 - The overall percentage of drivers braking was 25 percent when rumble strips were present (standard layout).
- TRS avoidance was minimal (3 percent).

Speed Measurement

Vehicle speeds were measured at two different locations—advance and after upstream TRS—as shown by the large red asterisks (*) in Figure 10.




Figure 10. Vehicle speed measurement locations relative to TRS setup locations

Speed Findings

Readers are cautioned to consider the limited number of speed observations per location when reviewing these results. Table 4 summarizes the results of the speed data collected at the advance location by layout, roadway, and overall.

Table 4. Advance location speeds

	Setup		
	No TRS	Standard	Modified
Advance - IA 92			
Number of Vehicles	196	998	274
Mean (mph)	52.1	53.7*	54.5*
85th Percentile speed (mph)	59.5	60.6	60.8
Standard Deviation	7.6	7.7	6.9
Advance - US 52			
Number of Vehicles	188	485	216
Mean (mph)	49.4	51.5*	51.7*
85th Percentile speed (mph)	60.9	60.2	58.6
Standard Deviation	13.4	11.6	6.4
Advance - All			
Number of Vehicles	384	1483	490
Mean (mph)	50.8	53.0*	53.3*
85th Percentile speed (mph)	60.0	60.4	60.1
Standard Deviation	10.9	9.2	6.8

* Statistically significant change from no rumble strips

Table 5 summarizes the results of the speed data collected after the upstream TRS location by setup, roadway, and overall.

Table 5. After upstream TRS speeds

	Setup		
	No TRS	Standard	Modified
After upstream TRS - IA 92			
Number of Vehicles	205	908	494
Mean (mph)	56.4	46.8*	49.5*
85th Percentile speed (mph)	61.0	55.5	56.7
Standard Deviation	5.7	8.7	7.5
After upstream TRS - US 52			
Number of Vehicles	253	335	194
Mean (mph)	46.5	49.5*	49.8*
85th Percentile speed (mph)	55.7	59.0	57.3
Standard Deviation	8.8	10.3	7.4
After upstream TRS - All			
Number of Vehicles	458	1243	688
Mean (mph)	50.9	47.5*	49.6*
85th Percentile speed (mph)	59.4	56.6	56.9
Standard Deviation	9.0	9.3	7.4

* Statistically significant change from no rumble strips

Table 6 summarizes the results of the speed data collected by roadway and overall.

Table 6. Impact on mean speeds

Setup	Mean Speed (mph)		
	Advance	After Upstream TRS	Change
IA 92			
No TRS	52.1	56.4	4.3*
Standard	53.7	46.8	-6.9*
Modified	54.5	49.5	-5.0*
US 52			
No TRS	49.4	46.5	-2.9*
Standard	51.5	49.5	-2.0*
Modified	51.7	49.8	-1.9*
All			
No TRS	50.8	50.9	0.1
Standard	53.0	47.5	-5.5*
Modified	53.3	49.6	-3.7*

* Statistically significant change from advance to after upstream TRS setup

These results show that, overall, drivers are slowing down from the advance location to the observed point after the first set of TRS. These reductions were statistically significant at -5.5 mph and -3.7 mph for the standard and modified layout, respectively.

SUMMARY

These limited-scale field measurements were conducted to quantify the impact of the TRS setups at two different construction projects. The field work was not designed to produce statistically valid comparisons for TRS effectiveness, nor contrast between TRS layouts, project locations, or measured locations per site.

It is important the reader does not misinterpret these findings as comprehensive nor consistent with any type of before/after or test/control evaluation (these are only measurements). Given the above limitations, the presence of temporary rumble strips were found to have the following impacts as vehicles approached the work zones:

- Increased driver braking
- Minimal driver avoidance
- Reduced vehicle speeds

These field data are considered positive and should serve future study efforts in terms of hypothesis development and testing as part of a controlled evaluation.