

DEVELOPMENT OF A SLAB-ON-GIRDER WOOD-CONCRETE COMPOSITE HIGHWAY BRIDGE



Andrew Lehan



David Moses






International Conference on Timber Bridges 2013

Las Vegas, NV

September 2013

THE ``PROPOSED CONCEPT``



- Slab-on-girder bridge superstructure
- Vehicular bridge
- Applied loads as per the Canadian Highway Bridge Design Code
- Designed for spans ranging from 10 m – 30 m in 5 m increments

Development of a Slab-on-Girder Wood-Concrete Composite Highway Bridge

Andrew Lehan, Delcan   & David Moses, Moses Structural Engineers



THE NEED FOR A WOOD-CONCRETE COMPOSITE BRIDGE?


- Wood bridges are rare in Canada in spite of a large forestry industry
- Advancements in material technology afford longer span opportunities for wood bridges:
 - Ultra-high performance fibre-reinforced concrete
 - External unbonded post-tensioning
- Slab-on-girder bridges are common in Canada
- Cast-in-place concrete is scarce in many remote regions

Development of a Slab-on-Girder Wood-Concrete Composite Highway Bridge

Andrew Lehan, Delcan  & David Moses, Moses Structural Engineers




ROADWAY CROSS-SECTION



Roadway cross-section valid for:

- 1) an undivided local rural road with a speed limit of 100 km/h
- 2) an undivided urban collector road with a speed limit of 80 km/h

STRUCTURAL CROSS-SECTION



CROSS-SECTION IN-BETWEEN DIAPHRAGMS


- Four double-T modules
- Eight glued-laminated girders
- 110 mm thick ultra-high performance fibre-reinforced concrete deck
- Composite action between deck and girders
- Longitudinal and transverse post-tensioning

Development of a Slab-on-Girder Wood-Concrete Composite Highway Bridge


Andrew Lehan, Delcan  & David Moses, Moses Structural Engineers




PRESTRESSING CONCEPT



Longitudinal Tendon Profile




Tendon Deviator




End Buttruss

Development of a Slab-on-Girder Wood-Concrete Composite Highway Bridge

DIAPHRAGMS



CROSS-SECTION AT DIAPHRAGMS



- Cast monolithically with deck slab
- Improve live load distribution between girders
- House transverse post-tensioning ducts & anchorages

Development of a Slab-on-Girder Wood-Concrete Composite Highway Bridge


Andrew Lehan, Delcan



& David Moses, Moses Structural Engineers




CONSTRUCTION SEQUENCE




Stage 1

- Erect modules



Stage 2

- Stress transverse & longitudinal tendons





Stage 3

- Construct curbs & barrier
- Pave deck

Development of a Slab-on-Girder Wood-Concrete Composite Highway Bridge

ULTRA-HIGH PERFORMANCE FIBRE-REINFORCED CONCRETE



Benefits:


- Allows for slender slab, unlike conventional concrete
- High tensile strength precludes most passive reinforcement
- Very low permeability (enhances durability)
- Excellent freeze-thaw resistance (enhances durability)

Development of a Slab-on-Girder Wood-Concrete Composite Highway Bridge

Andrew Lehan, Delcan   & David Moses, Moses Structural Engineers




COMPOSITE ACTION



- Proposed concept is a partially-composite system

LONGITUDINAL SHEAR CONNECTOR




Idealized Connector Behaviour

Span	% Composite Action
10 m	87%
15 m	92%
20 m	95%
25 m	96%
30 m	87%

- Idealized behaviour is supported by experimental evidence
- Nearly full composite action is attainable


SUMMARY OF THE PROPOSED CONCEPT



Span	Depth	Span-to-Depth Ratio
10 m	0.56 m	17.9
15 m	0.76 m	19.7
20 m	0.91 m	22.0
25 m	1.11 m	22.5
30 m	1.26 m	23.8

Development of a Slab-on-Girder Wood-Concrete Composite Highway Bridge

SLAB-ON-CPCI-GIRDER BRIDGES




TYPICAL CROSS-SECTION

Development of a Slab-on-Girder Wood-Concrete Composite Highway Bridge


Andrew Lehan, Delcan   & David Moses, Moses Structural Engineers




COMPARISON TO SLAB-ON-CPCI-GIRDER BRIDGES




Superstructure Weight



Slenderness



Volume of Cast-in-Place Concrete



CONCLUSIONS RELATIVE TO SLAB-ON-CPCI-GIRDER BRIDGES

1) The Proposed Concept is half as heavy

- Less expensive foundations
- Less expensive transportation of materials to site
- Lesser inertial forces during seismic event

2) The Proposed Concept uses much less cast-in-place concrete

- Shorter duration of on-site construction
- Likely more durable

3) The Proposed Concept is much more slender

- Greater structural efficiency
- Less approach fill and shallower fill retaining structures